

## GS# CT-20 Sealant

### Technical Data Sheet

#### PRODUCT DESCRIPTION

GS# CT-20 Sealant is a non-hardening butyl tape that forms and immediate and permanent bond to virtually any clean and dry surface. This high performance, high rubber content sealant provides excellent structural support as well as long life expectancy. GS# CT-20 Sealant remains permanently flexible while exposed to extreme temperature fluctuations, will self-heal around bolts and fasteners after it has been punctured, and is extremely weather resistant.

#### PRODUCT ADVANTAGES

- High rubber content which provides excellent structural support
- Non-Hazardous
- Fast and easy to apply by hand
- Excellent weathering characteristics
- Tenacious surface adhesion
- Service temperature of -40°F to 180°F (-40°C to 82°C)

#### APPLICATION

Surface should be free of moisture, oil and dust for maximum bond. Apply the sealant by hand to the application surface and press the sealant into place with the release liner still adhered to the sealant on one side to prevent contamination. Remove release liner when ready to apply the sealant to remaining application site. Ideal application temperature is 45°F (7°C) or above.

Product is not considered hazardous to skin however wash hands before eating. DO NOT TAKE INTERNALLY.



#### TYPICAL PHYSICAL PROPERTIES

<b>Chemical Base</b>	Butyl Rubber
<b>Color</b>	Black
<b>Specific Gravity (ASTM D 792)</b>	1.36
<b>Total Solids</b>	100%
<b>Penetration (ASTM D 217) cone at 72°F / 150 grams</b>	55-65 (5.5 to 6.5 mm)
<b>Rolling Ball Tack (ASTM D 3121)</b>	3.0 cm max (11/16" Ball)
<b>Flexibility (ASTM C 765)</b>	No cracking or loss of adhesion at -10°F (-23°C) when bent around 3/8" mandrel (9.5mm)
<b>Staining (ASTM D 925)</b>	Will not stain painted or unpainted surfaces
<b>Odor (ASTM D 1833)</b>	None
<b>Vehicle Bleed Out (ASTM C 772)</b>	No exudation of vehicle on Whatman No. 40 filter paper
<b>Crazing to Acrylic Plastics</b>	Will not craze plastics
<b>Resistance to Fungus/Mildew Growth</b>	Will resist fungal attack and mildew growth
<b>Tensile Adhesive Strength (ASTM C 907)</b>	7 psi (typical failure mode 100% cohesive)

## GS# CT-20 Sealant

### Technical Data Sheet

#### TYPICAL PHYSICAL PROPERTIES CONTINUED

<b>Adhesion</b>	Excellent
<b>Water Resistance</b>	Excellent
<b>Corrosivity</b>	Aluminum: None Galvanized Metal: None
<b>Service Temperature</b>	-40°F to 180°F (-40°C to 82°C)
<b>Shelf Life (Storage at 72°F/ 22°C)</b>	1 Year from DOM

NOTE: TECHNICAL INFORMATION AND DATA SHOULD BE CONSIDERED REPRESENTATIVE OR TYPICAL ONLY AND SHOULD NOT BE USED FOR SPECIFICATION PURPOSES.

#### PACKAGING

GS# CT-20 Sealant is available in a wide range of extruded sizes supplied in roll form on a release liner.

#### STORAGE AND HANDLING

Material should be stored at 72°F (22°C) in a dry area in its original sealed case and case must remain right side up.

For more information on GS# CT-20 Sealant, please email [Sales@GeneralSealants.com](mailto:Sales@GeneralSealants.com) or call (800)-762-1144 to speak with our Sales Department.

#### USER'S RESPONSIBILITY

THIS PRODUCT INFORMATION CANNOT COVER ALL POSSIBLE SITUATIONS, WHICH THE USER MAY EXPERIENCE DURING PROCESSING. EACH ASPECT OF YOUR OPERATION SHOULD BE EXAMINED TO DETERMINE IF, OR WHERE, ADDITIONAL PRECAUTIONS MAY BE NECESSARY. ALL HEALTH AND SAFETY INFORMATION CONTAINED IN THIS BULLETIN SHOULD BE PROVIDED TO YOUR EMPLOYEES OR CUSTOMERS. IT IS YOUR RESPONSIBILITY TO USE THIS INFORMATION TO DEVELOP APPROPRIATE WORK PRACTICE GUIDELINES AND EMPLOYEE INSTRUCTIONAL PROGRAMS FOR YOUR OPERATION.

#### DISCLAIMER OF LIABILITY

AS THE CONDITIONS OR METHODS OF USE ARE BEYOND OUR CONTROL, WE DO NOT ASSUME ANY RESPONSIBILITY AND EXPRESSLY DISCLAIM ANY LIABILITY FOR ANY USE OF THIS MATERIAL. INFORMATION CONTAINED HEREIN IS BELIEVED TO BE TRUE AND ACCURATE BUT ALL STATEMENTS OR SUGGESTIONS ARE MADE WITHOUT WARRANTY, EXPRESSED OR IMPLIED, REGARDING THE ACCURACY OF THE INFORMATION, THE HAZARDS CONNECTED WITH THE USE OF THE MATERIAL OR THE RESULTS TO BE OBTAINED FROM THE USE THEREOF. COMPLIANCE WITH ALL APPLICABLE FEDERAL, STATE, AND LOCAL LAWS AND REGULATIONS REMAINS THE RESPONSIBILITY OF THE USER.

#### CONFIDENTIALITY NOTICE

THIS DOCUMENT CONTAINS CONFIDENTIAL INFORMATION BELONGING TO THE SENDER, WHICH IS LEGALLY PRIVILEGED. THE INFORMATION IS INTENDED ONLY FOR THE USE OF THE INDIVIDUAL OR ENTITY NAMED ABOVE. IF YOU ARE NOT THE INTENDED RECIPIENT, BE AWARE THAT ANY DISCLOSURE, COPYING, DISTRIBUTION OR USE OF THIS INFORMATION IS PROHIBITED. IF YOU HAVE RECEIVED THIS IN ERROR, PLEASE CONTACT US IMMEDIATELY AND DELETE (DESTROY) THE DOCUMENT.

#### WARRANTY

PRODUCTS ARE SOLD WITHOUT WARRANTY, EXPRESSED OR IMPLIED, EXCEPT IF SHOWN TO BE DEFECTIVE IN MATERIALS WITHIN 30 DAYS OF SHIPMENT BY GENERAL SEALANTS, IT WILL BE REPLACED OR AT GENERAL SEALANTS OPTION THE PURCHASE PRICE WILL BE REFUNDED TO THE PURCHASER. GENERAL SEALANTS ASSUME NO RESPONSIBILITY FOR CONSEQUENTIAL DAMAGE ARISING FROM THE USE OF OUR PRODUCTS. USER MUST CONFIRM THE ADAPTABILITY OF OUR PRODUCTS BY THEIR OWN TEST. NO REPRESENTATIVE OF GENERAL SEALANTS OR ANY OTHER COMPANY HAS AUTHORIZATION TO GRANT ANY ADDITIONAL WARRANTY